

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/047125 A1

(51) International Patent Classification⁷: H01C 7/18

(21) International Application Number:
PCT/SE2003/001786

(22) International Filing Date:
18 November 2003 (18.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/299,022 19 November 2002 (19.11.2002) US

(71) Applicant (for all designated States except US): ABB AB
[SE/SE]; Kopparbergsvägen 2, S-721 83 Västerås (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): EKWALL, Oile
[SE/SE]; Plommonstigen 27, S-771 43 Ludvika (SE).

(74) Agent: ABB AB; Legal & Compliance/Intellectual Prop-
erty, Forskargränd 8, S-721 78 Västerås (SE).

(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, EG, ES, FI (utility model), FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK (utility model), SK, SI, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A LIQUID-COOLED HIGH-POWER RESISTOR



(57) Abstract: A high-power resistor comprises a plurality of resistor elements (1), made of sheets of an electrically conductive resistance material, with a first (13) and a second (14) terminal. The resistor elements are mutually separated by disc-shaped insulating first shims (2). Said first and second terminals are connected to adjacently located resistor elements so that the respective first terminals are connected to a first terminal and that the respective second terminals are connected to a second terminal. Two adjacent resistor elements form a current path, whereby, viewed in a direction perpendicular to the plane of the sheets, said first and second terminals, respectively, are so mutually positioned that, for a current supplied thereto, the current path in one resistor element substantially overlaps the current path in an adjacent resistor element and hence carries current in mutually opposite directions in the two adjacent resistor elements.

WO 2004/047125 A1